

GTEK[™] COMPOUND TECHNICAL SHEET

GTEK[™] Masonry Adhesive is a specially formulated cement designed to fix plasterboard to masonry, concrete and brick surfaces.

GTEK[™] Masonry Adhesive

- ▶ Strong and fast adhesive
- ▶ Fixes plasterboard quickly and securely
- ▶ Available in a setting time of 80 minutes



GTEKTM COMPOUND TECHNICAL SHEET

Preparation

Always use clean appropriate containers to mix Masonry Adhesive. Use only clean domestic water and do not add more water after the mixture begins to set.

Mixing

Add Masonry Adhesive to water and mix to a creamy consistency. Use the proportion of approximately 3kg Masonry Adhesive 80 to 1.5 litres of water. Do not add other raw materials as this can affect the performance of the Masonry Adhesive.

Do not mix more material than can be used in 80 minutes.

Application

Masonry Adhesive can be applied to either the plasterboard sheets or to the wall surface. Leveling pads should be used where deformities in the wall exceed 15mm.

Apply Masonry Adhesive in 50mm daubs standing out approximately 15mm. Space the daubs at 450mm centers and not more than 50mm from sheet edges.

Place the plasterboard sheet in position and hold until the Masonry Adhesive sets.

Masonry Adhesive should not be used in installation of fire rated or wet areas systems.

