

GTEKTM COMPOUND TECHNICAL SHEET

GTEKTM Masonry Adhesive is a specially formulated plaster based adhesive designed to fix plasterboard to masonry, concrete and brick surfaces.

GTEKTM Masonry Adhesive

- ▶ Strong and fast adhesive
- ▶ Fixes plasterboard quickly and securely
- ▶ Available in a setting time of 90 - 110 minutes



GTEK™ COMPOUND TECHNICAL SHEET

Preparation

Always use clean appropriate containers to mix GTEK™ Masonry Adhesive. Use only clean domestic water and do not add more water after the mixture begins to set.

Mixing

Add GTEK™ Masonry Adhesive to water and mix to a creamy consistency. Use the proportion of approximately 3kg GTEK™ Masonry Adhesive 100 to 1.5 litres of water. Do not add other raw materials as this can affect the strength and performance of the GTEK™ Masonry Adhesive.

Do not mix more GTEK™ Masonry Adhesive than can be used in 100 minutes.

Application

GTEK™ Masonry Adhesive can be applied to either the plasterboard sheets or to the wall surface. Leveling pads should be used where deformities in the wall exceed 15mm.

Apply GTEK™ Masonry Adhesive in 50mm daubs standing out approximately 15mm. Space the daubs at 450mm maximum centres and not more than 50mm from sheet edges.

Place the plasterboard sheet in position and allow the GTEK™ Masonry Adhesive to set.

Allow daubs to set for minimum 100 minutes prior to any further work. For wet areas that are to be tiled, see GTEK™ Smartwall brochure.

